



TILE CARE

TILE ADHESIVES & CONSTRUCTION CHEMICALS

Tile Adhesives | Grouts | Epoxy Systems
Tile Care Solutions | Installation Accessories



HIGH
BOND STRENGTH



WATER
RESISTANT



EASY
APPLICATION



PROFESSIONAL
GRADE



TRUSTED
QUALITY



PREMIUM
QUALITY



ADVANCED
FORMULATION



TESTED FOR
PERFORMANCE



SAFE FOR YOU
& ENVIRONMENT

**HAR TILE KA
PAKKA SAATHI!**

CLEANING SOLUTIONS

TRIKASHI KLEEN PRO



TRIKASHI KLEEN PRO is a powerful cleaning solution specially formulated for removing cement stains, grout residue and construction dirt from tiles and stone surfaces. Its advanced formula effectively cleans surfaces without damaging tile finish, restoring the original donsa shine and appearance. The product is easy to use and ideal for professional tile cleaning and post-construction cleaning applications.

Suitable For:

- Ceramic Tiles
- Vitrified Tiles
- Marble & Granite Surfaces
- Removing Cement & Grout Stains
- Post Construction Cleaning
- Residential & Commercial Applications

Technical Details

Parameters	Appearance	Application Type	Surface Compatibility	Usage Method
Specification	Liquid Cleaner	Tile & Stone Cleaning	Ceramic, Vitrified, Marble, Granite	Direct Application / Diluted Use

Coverage: Coverage depends on surface condition and level of staining.



TILE CLEANER

TRIKASHI MAGIC CLEAN TILE CLEANER



TRIKASHI MAGIC CLEAN TILE CLEANER is a superior quality, powerful cleaner specially formulated to remove tough stains, dirt, grease, soap scum and hard water deposits from all types of tile surfaces. Its advanced formula deep cleans without damaging the tiles and leaves the surface shining bright and hygienic. Ideal for regular use in bathrooms, kitchens and other tiled areas.

Suitable For:

- Ceramic Tiles
- Vitrified Tiles
- Porcelain Tiles
- Marble & Granite
- Bathroom & Kitchen Surfaces
- Wall & Floor Tiles
- Interior & Exterior Areas

Technical Details

Parameters	Appearance	pH Value (1% Solution)	Dilution Ratio	Coverage	Application Method
Specification	Clear Liquid	10.0 – 11.0	1:10 to 1:20 (With Water)	80 – 100 sq.ft. / Ltr.	Apply, Scrub & Rinse

PU ADHESIVE / SEALANT

TRIKASHI PUA 555



TRIKASHI PUA 555 is a high-performance polyurethane adhesive and sealant designed for strong bonding, sealing and flexible joint applications in construction projects. Its advanced PU formulation provides excellent adhesion, weather resistance and long-lasting durability on various construction surfaces. The product ensures reliable sealing and bonding performance for both interior and exterior applications.

Suitable For:

- Concrete Surfaces
- Metal & Aluminum
- Stone & Marble
- Tile & Construction Joints
- Interior & Exterior Sealing
- Residential & Commercial Applications

Technical Details

Parameters	Appearance	Adhesion Strength	Flexibility	Setting Time	Application Type
Specification	PU Based Sealant	High Strength Bond	Flexible	Approx. 24 hours	Bonding & Sealing Applications

Coverage: Coverage depends on joint size and application thickness.

ADMIXO

TRIKASHI ADMIXO POLYMER ADDITIVE



TRIKASHI ADMIXO is a high-performance polymer additive designed to be mixed with cement-based tile grouts to enhance their performance and durability. It improves strength, flexibility and reduces water permeability, making grout joints more waterproof, shrink-resistant and long-lasting. It ensures excellent bonding and superior resistance to cracks, efflorescence and wear, providing a reliable and cost-effective solution for all tiling applications.

Suitable For:

- Ceramic Tiles
- Vitrified Tiles
- Wall Tile Joints
- Floor Tile Joints
- Residential & Commercial Application
- Interior & Exterior Use

Technical Details

Parameters	Appearance	Dosage	Key Benefit	Compatibility
Specification	White Emulsion Liquid	400 ml per 5 kg grout	Improves Strength, Flexibility & Water Resistance	Compatible with Cement Based Grouts

BLOCK JOINING MORTAR

BLOCK JOINING MORTAR 085



BLOCK JOINING MORTAR 085 is a high-quality ready-mix cement based mortar specially designed for joining AAC blocks, fly ash bricks and concrete blocks. Its advanced formulation provides strong bonding, smooth workability and thin joint application, ensuring faster construction and durable masonry work. The product improves structural strength while reducing material consumption, making it ideal for modern construction projects.

Suitable For:

- AAC Blocks
- Fly Ash Bricks
- Concrete Blocks
- Masonry Construction
- Residential & Commercial Buildings
- Interior & Exterior Walls

Technical Details

Parameters	Specification
Appearance	Grey Powder
Joint Thickness	3mm - 5mm
Compressive Strength	High Strength
Setting Time	Approx. 24 hours
Application Type	Block Masonry Work

Coverage:

Approx. 35-40 sq.ft. per 40 kg bag depending on block size and joint thickness.

EPOXY ADHESIVE

TRIKASHI EP-2K



TRIKASHI EP-2K is a premium two-component epoxy adhesive specially formulated for high strength bonding and long-lasting performance. Its advanced epoxy formulation ensures excellent adhesion to tiles, stone, concrete and other construction surfaces. The product provides superior durability, chemical resistance and reliable bonding, making it suitable for demanding residential and commercial construction applications.

Suitable For:

- Ceramic Tiles
- Marble & Granite
- Stone Fixing
- Concrete Surfaces
- Industrial & Commercial Applications
- Heavy Duty Bonding

Technical Details

Parameters	Appearance	Adhesion Strength	Working Time	Setting Time	Application Type
Specification	Two Component Epoxy	High Strength Bond	Approx. 30 minutes	24 hours	Wall & Floor Applications

Coverage: Coverage depends on surface type and application thickness.

TILE SPACER

TRIKASHI TILE SPACER 4MM



TRIKASHI TILE SPACER 4MM is a precision-engineered tile spacer designed to ensure uniform spacing and perfect alignment between tiles. Made from high-quality virgin plastic, it provides excellent strength, durability and shape retention. It helps achieve a professional finish with even grout lines and reduces lippage during tile installation. Ideal for all types of ceramic, vitrified, porcelain and natural stone tiles.

Suitable For:

- Ceramic Tiles
- Vitrified Tiles
- Porcelain Tiles
- Wall Tile Joints
- Floor Tile Joints
- Residential & Commercial Application
- Interior & Exterior Use

Technical Details

Parameters	Appearance	Joint Width	Material	Pack Size	Application Type
Specification	Cross Shape	4mm	High Grade Virgin Plastic	100 Nos. (Bag)	Wall & Floor Tile Joints

EPOXY ADHESIVES

ULTRA STRONG STANDARD EPOXY ADHESIVE



ULTRA STRONG STANDARD EPOXY ADHESIVE is a high-performance two-component epoxy adhesive designed for extremely strong bonding and long-lasting durability. It provides excellent adhesion to tiles, stone, concrete and various construction materials. The advanced epoxy formulation ensures high strength, chemical resistance superior performance for demanding applications in residential and commercial construction projects.

Suitable For:

- Ceramic Tiles
- Granite & Marble
- Stone Fixing
- Concrete Surfaces
- Industrial & Commercial Applications
- Heavy Duty Bonding

Technical Details:

Parameters	Appearance	Adhesion Strength	Working Time	Setting Time	Application Type
Specification	Two Component Epoxy	High Strength Bond	Approx. 30 minutes	24 hours	Wall & Floor Applications

Coverage: Coverage depends on surface type and application thickness.

TILE GROUT

Tile - O - Grout



Trikashi Tile-o-Grout is a high-quality cement based tile grout designed for filling tile joints with strong bonding and smooth finishing. Its advanced formulation provides excellent durability, crack resistance and water resistance, ensuring long-lasting tile joint protection. The product enhances the appearance of tiled surfaces and delivers reliable performance for both residential and commercial tile installations.

Suitable For:

- Ceramic Tiles
- Vitrified Tiles
- Wall Tile Joints
- Floor Tile Joints
- Residential & Commercial Application
- Interior Tile Grouting

Technical Details

Parameters	Appearance	Joint Width	Compressive Strength	Setting Time	Application Type
Specification	Fine Powder	1mm – 6mm	High Strength	Approx. 24 hours	Wall & Floor Tile Joints

Coverage: Coverage depends on tile size and joint width.

TILE INSTALLATION TOOLS

PROFESSIONAL LEVELING & WEDGES



PROFESSIONAL LEVELING & WEDGES is a high-quality tile leveling system designed to ensure perfectly aligned tiles and an even surface during installation. The system helps prevent tile lippage and provides consistent spacing between tiles, resulting in a smooth and professional finish. Made from durable materials, it improves installation speed and accuracy, making it ideal for both professional contractors and residential tile installation projects.

Suitable For:

- Ceramic Tiles
- Vitrified Tiles
- Large Format Tiles
- Wall & Floor Tile Installation
- Professional Tile Installation
- Residential & Commercial Projects

*Technical Details

Parameters	Material	Usage	Tile Thickness	Application Type
Specification	High Strength Plastic	Tile Leveling System	3mm – 12mm	Wall & Floor Installation

*Coverage / Usage:

Used with leveling clips and wedges to maintain even tile alignment during installation.

EPOXY ADHESIVE

Tile Care EpogROUT



TriKashi EpogROUT is a high-performance two-component epoxy adhesive designed for extremely strong bonding and long-lasting durability. Its advanced formulation offers excellent adhesion to tiles, stone, concrete and various construction mate. The product provides superior chemical resistance, high bonding strength and reliable performance, making it ideal for heavy-duty residential and commercial construction applications.

Suitable For:

- Ceramic Tiles
- Marble & Granite
- Stone Fixing
- Concrete Surfaces
- Industrial & Commercial Applications
- Heavy Duty Bonding

Technical Details

Parameters	Appearance	Adhesion Strength	Working Time	Setting Time	Application Type
Specification	Two Component Epoxy	High Strength Bond	Approx. 30 minutes	24 hours	Wall & Floor Applications

Coverage: Coverage depends on surface type and application thickness.

TILE ADHESIVES

Normal Application (Grey)



Normal Application (Grey) is a high-performance polymer modified cement based tile adhesive developed for superior bonding and reliable tile installation. Its advanced formulation ensures strong adhesion, smooth workability and excellent durability for fixing ceramic and vitrified tiles on walls and floors. The product provides long-lasting performance and professional finish, making it suitable for residential and commercial construction applications.

Suitable For:

- Ceramic Tiles
- Vitrified Tiles
- Internal Flooring
- Wall & Floor Tile Fixing
- Residential & Commercial Application
- Dry Area Installation

Technical Details

Parameters	Appearance	Tensile Adhesion Strength (28 days)	Shear Adhesion Strength (28 days)	Open Time	Pot Life
Specification	Grey Powder	1.00-1.15 N/mm ²	1.25-1.40 N/mm ²	Approx. 25 minutes	>2 hours

Coverage:

45-55 sq.ft. per 20 kg bag at 3mm bed thickness.

TILE ADHESIVES

Normal Application (White)



Normal Application (white) is a premium quality white cement based polymer modified tile adhesive designed for superior bonding and long-lasting tile installation. Its advanced formulation provides excellent adhesion strength, smooth workability and high durability for fixing ceramic, vitrified and light colored tiles on walls and floors. The product ensures strong grip and professional finish, making it ideal for residential and commercial tile fixing applications.

Suitable For:

- Ceramic Tiles
- Vitrified Tiles
- Marble & Light Colored Stones
- Wall & Floor Tile Fixing
- Residential & Commercial Application
- Dry Area Installation

Technical Details

Parameters	Appearance	Tensile Adhesion Strength (28 days)	Shear Adhesion Strength (28 days)	Open Time	Pot Life
Specification	White Powder	1.00–1.15 N/mm ²	1.25–1.40 N/mm ²	Approx. 25 minutes	>2 hours

Coverage:

45–55 sq.ft. per 20 kg bag at 3mm bed thickness.

TILE ADHESIVES

Type 02 for 4*2 N Above (Grey)



Type 02 for 4*2 N Above is a high-performance polymer modified cement based tile adhesive designed for strong bonding and reliable tile fixing. Its advanced formulation provides excellent strength, smooth workability and long-lasting durability for fixing ceramic and vitrified tiles on walls and floors. The product ensures stable grip and professional finish, making it ideal for all residential as well as commercial tile installation projects.

Suitable For:

- Ceramic Tiles
- Vitrified Tiles
- Internal Flooring
- Wall & Floor Tile Fixing
- Residential & Commercial Application
- Dry Area Installation

Technical Details

Parameters	Appearance	Tensile Adhesion Strength (28 days)	Shear Adhesion Strength (28 days)	Open Time	Pot Life
Specification	Grey Powder	1.00-1.15 N/mm ²	1.25-1.40 N/mm ²	Approx. 25 minutes	>2 hours

Coverage: 45-55 sq.ft. per 20 kg bag at 3mm bed thickness.

TILE ADHESIVES

Type 02 for 4*2 N Above (White)



Type 02 for 4*2 N Above is a premium quality white cement based tile adhesive formulated for superior bonding and long lasting tile installation. Its advanced polymer modified composition ensures excellent grip, smooth workability and strong adhesion for fixing ceramic, vitrified and light colored tiles on walls and floors. The product provides reliable performance and durability, making it suitable for residential as well as commercial tile fixing applications.

Suitable For:

- Ceramic Tiles
- Vitrified Tiles
- Marble & Light Colored Stones
- Wall & Floor Tile Fixing
- Residential & Commercial Application
- Dry Area Installation

Technical Details

Appearance	White Powder
Tensile Adhesion Strength (28 days)	0.90–1.10 N/mm ²
Shear Adhesion Strength (28 days)	1.20–1.35 N/mm ²
Open Time	Approx. 25 minutes
Pot Life	>2 hours

Coverage:

45–55 sq.ft. per 20 kg bag at 3mm bed thickness.

TILE ADHESIVES

GREY PLATINUM 095



GREY PLATINUM 095 is a high-quality polymer modified cement based tile adhesive designed for strong bonding and durable tile installation. It provides excellent adhesion strength, smooth application and reliable performance for fixing ceramic and vitrified tiles on walls and floors. The advanced formulation ensures long-lasting durability and easy workability, making it suitable for residential and commercial construction projects.

Suitable For:

- Ceramic Tiles
- Internal Flooring
- Vitrified Tiles
- Wall & Floor Tile Fixing
- Residential & Commercial Application
- Dry Area Installation

Technical Details

Specification

Appearance	Grey Powder
Tensile Adhesion Strength	0.90–1.00 N/mm ²
Shear Adhesion Strength (28 days)	1.20–1.30 N/mm ²
Open Time	Approx. 25 minutes
Pot Life	>2 hours

Coverage:

45–55 sq.ft. per 20 kg bag at 3mm bed thickness.

TILE ADHESIVES

WHITE PLATINUM



WHITE PLATINUM is a premium quality white cement based tile adhesive specially designed for fixing ceramic, marble and light colored tiles. It offers superior bonding strength, smooth smooth workability and long-lasting durability. Its high-performance polymer formulation ensures excellent adhesion on cement screed screeds, plastered surfaces and concrete floors, making it ideal for both residential and commercial tile installations.

Suitable For:

- Ceramic Tiles
- Marble & Natural Stone
- Internal Flooring
- Wall Tile Fixing
- Residential & Commercial Application
- Dry Area Installation

Technical Details

Appearance	White Powder
Tensile Adhesion Strength (28 days)	0.90–1.00 N/mm ²
Shear Adhesion Strength (28 days)	1.20–1.30 N/mm ²
Open Time	Approx. 25 minutes
Pot Life	>2 hours

Coverage:

45–55 sq.ft. per 20 kg bag at 3mm bed thickness.